



ENGINEERED ROOF TRUSSES
 W/ ENERGY HEEL @ 2'-0" O.C.
 1/2" WATER BD. SHTG.
 1.5# FELT
 ICE & WATER SHIELD
 ASPHALT SHINGLES

*FIELD VERIFY ALL
 DIMENSIONS & CONDITIONS

2x6 TREATED SILL PLATE
 1/2" Ø ANCHOR BOLT
 @ 6'-0" O.C.
 SILL SEALER

5 CRS. 12" CONC. BLK.
 20" x 8" CONC. FTG.
 2x4 @ 16" O.C.
 R-11 FIBERGL. INSUL.
 VAPOR BARRIERS
 WATERPROOFING

2x6 SUBFASCIA
 ALUM. SOFTT & FASCIA
 CONT. SOFTT VENT
 RIGID WIND WASH BARRIER
 AIR CHUTE

2x6 @ 16" O.C.
 R-19 FIBERGL. INSUL.
 VAPOR BARRIER
 1/2" WATER SHTG.
 1/2" GYP. BD WALLS
 MATCH EXIST. SIDING

TYPICAL RIM JOIST NOTE
 HOLD THE RIM JOIST IN THE WIDTH
 OF THE RIGID INSULATION. (INSTALL RIGID
 INSULATION PER BUILDERS SPECS.)

12 CRS. 12" CONC. BLK.
 20" x 8" CONC. FTG.
 2x4 @ 16" O.C.
 FURRING WALL
 R-11 FIBERGL. INSUL.
 VAPOR BARRIERS
 WATERPROOFING

BUILDING SECTION
 SEE BUILDERS SPECIFICATION FOR BUILDING MATERIALS

3/8" = 1'-0"